



OPERATING RANGE

Water Liquid Ratio	0-100%
Gas Volume Fraction	0-100%
Operating Pressure	Up to 10,000 psi
Operating Temperature	-58-300 deg F
Liquid Range	Up to 65,000 BPD
Gas Range	0.05 – 36 MMscfd

SPECIFICATIONS

Meter Sizes	1.5"-6"
Flange Connection	ANSI 150#-2500#, Customized HP Flange
Density Measurement	Ba ¹³³ , 2mCi
Spool-Piece Length	9" (220mm) for 2" LiveFlo Ultra
Venturi Material	SS 316L, DSS, Inconel
Hazard Area Certification	UL Certified - Class I, DIV I or DIV II
Field Installations	Spool-Piece or Skid-Type
Power Supply	24 VDC / 110VAC
Communication Port	RS-232/RS-485/Ethernet
Communication Protocol	Modbus RTU or TCP
Remote Access	4G/LTE, Satellite
Data Gathering System	Can Integrate Existing Transmitter Data
Software	Customized Online Monitoring Platform

LiveFlo™

Multiphase Metering Solutions

Haimo America, Inc.
2901 Wilcrest Drive, Suite 285
Houston, Tx 77042
Office: +18328316623
www.goliveflo.com

